



## Bearing Load Table for Inquiry

1. Project / Structure name				
2. a) Type of bearing				
2. b) Bearing identification mark / position				
3. Quantity				
4. a) Seating material upper surface				
4. b) Seating material lower surface				
5. Design loads	ULS	vertical	max. (kN)	$N_{z,d} =$ <input type="text"/>
			min. (kN)	$N_{z,d} =$ <input type="text"/>
		longitudinal	max. (kN)	$V_{x,d} =$ <input type="text"/>
			transverse	max. (kN)
6. Displacement	ULS	longitudinal	max. (mm)	$v_{x,d} =$ <input type="text"/>
			min. (mm)	$v_{x,d} =$ <input type="text"/>
		transverse	max. (mm)	$v_{y,d} =$ <input type="text"/>
			min. (mm)	$v_{y,d} =$ <input type="text"/>
7. Rotation (radians)	ULS	longitudinal	max. (‰)	$\alpha_{x,d} =$ <input type="text"/>
			min. (‰)	$\alpha_{x,d} =$ <input type="text"/>
		transverse	max. (‰)	$\alpha_{y,d} =$ <input type="text"/>
			min. (‰)	$\alpha_{y,d} =$ <input type="text"/>
8. Limit dimensions of bearings (mm)				Length (x) <input type="text"/>
				Height (z) <input type="text"/>
				Width (y) <input type="text"/>